

PHASE CONTROL THYRISTORS

Stud Version

Features

- High current and high surge ratings
- $dv/dt = 1000V/\mu s$ option
- Glass-metal seal up to 1200V
- Threaded studs UNF 1/2"-20UNF-2A
- Types up to 1200V V_{RRM}/V_{DRM}
- $di/dt = 300A/\mu s$


110A

Typical Applications

- DC motor controls
- Controlled DC power supplies
- AC controllers

Major Ratings and Characteristics

Parameters	111RIA	Units
$I_{T(AV)}$	110	A
@ T_C	90	°C
$I_{T(RMS)}$	172	A
I_{TSM} @ 50Hz	2080	A
@ 60Hz	2180	A
I^2t @ 50Hz	21.7	KA ² s
@ 60Hz	19.8	KA ² s
V_{DRM}/V_{RRM}	400 to 1200	V
t_q typical	110	μs
T_J	- 40 to 140	°C



case style
TO-209AC (TO-94)

111RIA Series

Bulletin I25204 01/01

International
IR Rectifier

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code	V_{DRM}/V_{RRM} , max. repetitive peak and off-state voltage V	V_{RSM} , maximum non-repetitive peak voltage V	I_{DRM}/I_{RRM} max. @ $T_J = T_J$ max. mA
111RIA	40	400	500	20
	80	800	900	
	120	1200	1300	

On-state Conduction

Parameter		111RIA	Units	Conditions			
$I_{T(AV)}$	Max. average on-state current @ Case temperature	110	A	180° conduction, half sine wave			
		90	°C				
$I_{T(RMS)}$	Max. RMS on-state current	172	A	DC @ 83°C case temperature			
I_{TSM}	Max. peak, one-cycle non-repetitive surge current	2080		t = 10ms	No voltage	Sinusoidal half wave, Initial $T_J = T_J$ max.	
		2180		t = 8.3ms	reapplied		
		1750		t = 10ms	100% V_{RRM}		
		1830		t = 8.3ms	reapplied		
I^2t	Maximum I^2t for fusing	21.7	KA ² s	t = 10ms	No voltage		Sinusoidal half wave, Initial $T_J = T_J$ max.
		19.8		t = 8.3ms	reapplied		
		15.3		t = 10ms	100% V_{RRM}		
		14.0		t = 8.3ms	reapplied		
$I^2\sqrt{t}$	Maximum $I^2\sqrt{t}$ for fusing	217	KA ² √s	t = 0.1 to 10ms, no voltage reapplied			
$V_{T(TO)1}$	Low level value of threshold voltage	0.82	V	(16.7% x π x $I_{T(AV)}$ < I < π x $I_{T(AV)}$), $T_J = T_J$ max.			
$V_{T(TO)2}$	High level value of threshold voltage	1.02		(I > π x $I_{T(AV)}$), $T_J = T_J$ max.			
r_{t1}	Low level value of on-state slope resistance	2.16	mΩ	(16.7% x π x $I_{T(AV)}$ < I < π x $I_{T(AV)}$), $T_J = T_J$ max.			
r_{t2}	High level value of on-state slope resistance	1.70		(I > π x $I_{T(AV)}$), $T_J = T_J$ max.			
V_{TM}	Max. on-state voltage	1.57	V	I_{pk} = 350A, $T_J = T_J$ max., t_p = 10ms sine pulse			
I_H	Maximum holding current	150	mA	$T_J = 25^\circ\text{C}$, anode supply 6V resistive load			
I_L	Typical latching current	400					

Switching

Parameter	111RIA	Units	Conditions
di/dt Max. non-repetitive rate of rise of turned-on current	300	A/μs	Gate drive 20V, 20Ω, $t_r \leq 1\mu s$ $T_J = T_J$ max, anode voltage $\leq 80\% V_{DRM}$
t_d Typical delay time	1	μs	Gate current 1A, $di_g/dt = 1A/\mu s$ $V_d = 0.67\% V_{DRM}$, $T_J = 25^\circ C$
t_q Typical turn-off time	110		$I_{TM} = 50A$, $T_J = T_J$ max., $di/dt = -5A/\mu s$, $V_R = 50V$ $dv/dt = 20V/\mu s$, Gate 0V 25Ω

Blocking

Parameter	111RIA	Units	Conditions
dv/dt Maximum critical rate of rise of off-state voltage	500	V/ μ s	$T_J = T_J \text{ max. linear to } 80\% \text{ rated } V_{DRM}$
I_{RRM} I_{DRM} Max. peak reverse and off-state leakage current	20	mA	$T_J = T_J \text{ max, rated } V_{DRM}/V_{RRM} \text{ applied}$

Triggering

Parameter	111RIA	Units	Conditions
P_{GM} Maximum peak gate power	12	W	$T_J = T_J \text{ max, } t_p \leq 5\text{ms}$
$P_{G(AV)}$ Maximum average gate power	3.0		$T_J = T_J \text{ max, } f = 50\text{Hz, } d\% = 50$
I_{GM} Max. peak positive gate current	3.0	A	$T_J = T_J \text{ max, } t_p \leq 5\text{ms}$
$+V_{GM}$ Maximum peak positive gate voltage	20	V	$T_J = T_J \text{ max, } t_p \leq 5\text{ms}$
$-V_{GM}$ Maximum peak negative gate voltage	10		
I_{GT} DC gate current required to trigger	TYP.	MAX.	$T_J = -40^\circ\text{C}$ $T_J = 25^\circ\text{C}$ $T_J = 140^\circ\text{C}$ Max. required gate trigger/ current/ voltage are the lowest value which will trigger all units 12V anode-to-cathode applied
	180	-	
	80	120	
	40	-	
V_{GT} DC gate voltage required to trigger	2.5	-	$T_J = -40^\circ\text{C}$ $T_J = 25^\circ\text{C}$ $T_J = 140^\circ\text{C}$
	1.6	2	
	1	-	
I_{GD} DC gate current not to trigger	6.0	mA	$T_J = T_J \text{ max}$ Max. gate current/ voltage not to trigger is the max. value which will not trigger any unit with rated V_{DRM} anode-to-cathode applied
V_{GD} DC gate voltage not to trigger	0.25	V	

Thermal and Mechanical Specification

Parameter	111RIA	Units	Conditions
T_J Max. operating temperature range	-40 to 140	$^\circ\text{C}$	
T_{stg} Max. storage temperature range	-40 to 150		
R_{thJC} Max. thermal resistance, junction to case	0.27	K/W	DC operation
R_{thCS} Max. thermal resistance, case to heatsink	0.1		Mounting surface, smooth, flat and greased
T Mounting torque, $\pm 10\%$	15.5	Nm (lbf-in)	Non lubricated threads
	(137)		
	14 (120)		Lubricated threads
wt Approximate weight	130	g	
Case style	TO-209AC (TO-94)		See Outline Table

111RIA Series

Bulletin I25204 01/01

International
IRF Rectifier

ΔR_{thJC} Conduction

(The following table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction	Rectangular conduction	Units	Conditions
180°	0.043	0.031	K/W	$T_J = T_J \text{ max.}$
120°	0.052	0.053		
90°	0.066	0.071		
60°	0.096	0.101		
30°	0.167	0.169		

Ordering Information Table

Device Code				
11	1	RIA	120	
1	2	3	4	5
1	- $I_{T(AV)}$ rated average output current (rounded/10)			
2	- 0 = Eyelet terminals (Gate and Auxiliary Cathode Leads) 1 = Fast - on terminals (Gate and Auxiliary Cathode Leads) 2 = Flag terminals (For Cathode and Gate Terminals)			
3	- Thyristor			
4	- Voltage code: Code x 10 = V_{RRM} (See Voltage Rating Table)			
5	- Critical dv/dt: None = 500V/ μ sec S90 = 1000V/ μ sec			

Outline Table

GLASS-METAL SEAL FLAG TERMINALS	
Case Style TO-208AD (TO-83) All dimensions in millimeters (inches)	
* FOR METRIC DEVICE: M12 x 1.75 E 6	

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 4 - On-state Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristic




Fig. 9 - Gate Characteristics

111RIA Series

Bulletin I25204 01/01

International
IOR Rectifier

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 01/01